

# UNCG/UNHG

R-410A High-Efficiency Ductless Split System  
Universal Air Handlers


**EMI** *Ductless*

*Comfort Where It Counts.*

Straight cool / Heat pump nominal capacities			
<b>UNHG09</b>	<b>UNHG12</b>	<b>UNHG24</b>	Units
9,000	12,000	18,000 - 23,800	Btuh
2.6	3.5	5.3 - 7.0	kW
Straight cooling only — nominal capacity			
<b>UNCG30</b>		<b>UNCG36</b>	Units
28,200		33,600	Btuh
8.3		9.8	kW

## Specifications and Performance

*(with EMI condensers)*



ECR International Inc  
2201 Dwyer Ave  
Utica, NY 13501  
www.enviromaster.com  
email: info@enviromaster.com



An ISO 9001-2008 Certified Company


### NOTICE

EMI air handlers and condensers are backed by EMI and ECR International and are tested, rated and certified in accordance with ARI Standard 210/240 and UL-1995. Due to ongoing product development, product designs and specifications may change without notice. Please contact the factory for more information.

## UNCG/UNHG Air Handlers — Product Description

### Product description

- The UNCG/UNHG is available as a (DX) direct expansion straight cool and heat pump.
- It offers a contemporary design in a ductless type air handlers and combines attractive appearance with high efficiency conditioning for small to medium size commercial or residential spaces.
- The UNCG/UNHG is equipped with unit mounted infrared compatible controls which also supports 24V wall thermostat operation. Optional handheld remote is available.
- Heat pump models provide up to 23,800 Btuh of cooling and 20,600 Btuh of heating. Electric heat options are available for up to 5 kW of supplemental heat.
- These airhandlers offer ease of installation, operation, and service.
- It can be matched with EMI's:
  - Single-zone condensing units — S1CG/S1HG 9,000-24,000 Btuh and S1CG 36,000 Btuh.
  - Multi-zone condensing unit S2CG/S2HG 18,000-24,000 Btuh, T2CG/T2HG 27,000-48,000 Btuh, T3CG/T3HG 27,000-48,000 Btuh, T4CG/T4HG 36,000-48,000 Btuh
- All EMI air handlers are backed by ECR International Inc and are tested, rated and certified in accordance with ARI standards 210/240 and UL 1995.



- Modular design – reduces parts required for control package. Deco panel, relay board, ribbon cables and microprocessor are combined into one package.
- Integral condensate pump safety-switch connection where-by the microprocessor monitors the condensate pump safety switch and displays an error code when a fault occurs. (Applies only with optional condensate pump).
- CEC (California Energy Commission) compliant.
- Condensate drain pan over flow protection.

### Cabinet features:

- Easily accessible, washable, reusable, nylon mesh filter.
- Easy access to piping connections and condensate pump allows installation with the unit mounted in place.
- Condensate drain pan constructed of galvanized steel (G60U), with anti-corrosion coating.

### Optional equipment

- Floor mount trim kit.
- Condensate pump (field installed only).
- 24V wall thermostat.
- Electric heat with automatic reset high temperature cutout and redundant high temperature fuse link (when heat option is selected). 208/230V only.
- Hand-held infrared controller.
- Metal return air grille.

### Installer-supplied Items

- Low voltage wiring (18 AWG required).
- High voltage power supply wiring.
- Mounting screws and fasteners.
- Condensate piping.
- Refrigerant piping (if not supplied).
- Refrigerant (for interconnect charge).
- High voltage electrical disconnect.

### Controls and components (Factory-installed or supplied)

- Large LCD Backlit Display
- Single unit-mounted control package, configurable to either unit mount or wall thermostat operation, increasing installation flexibility.
- Unit control can be used in cooling only, cooling with electric heat, heat pump, or heat pump with second stage electric heat applications.
- Operational range set point temperature adjustable between 55°F and 90°F (13 to 32°C) in one-degree increments.
- Infrared-compatible controller allows use of optional IR hand held controller.
- Operation modes include Heat, Cool, Dry, Fan and Auto Change-over.
- Fan Operation – Auto/On, High or Low speed fan
- Fan Purge – Fan remains on for 60 seconds after Heat/Cool call is dropped for improved efficiency (Auto mode only)
- Room air sampling — Selectable time intervals ensure the fan will cycle on periodically, in Auto Fan Mode to help eliminate room temperature stratification.
- Selectable Fahrenheit (°F) or Celsius (°C) temperature scale.
- Dry mode – Operates cooling and electric heat simultaneously to remove humidity. Optional electric heat must be selected.
- Anti-Short Cycle Compressor Protection.
- Minimum on time for heating and cooling helps eliminate room temperature drop and system short cycling.
- Freeze Protection – Prevents air handlers freeze up.
- Test operation – Allows ease of testing after installation (all timers are reduced).
- Non-volatile back-up memory will maintain control settings for an indefinite period during a power outage. When power is restored the equipment will resume operation after a three-minute compressor time delay.
- 7-day, 4 event programmable with copy feature.
- Filter change indicator: A timer feature indicates when the filter should be cleaned according to the selected time.

**Table 1** Condensate pump kit option — part numbers

Floor-mounted units			Ceiling-mounted units		
Air handler	208/230v	115v	Air handler	208/230v	115v
09/12	550001727	550001728	09/12	240006200	240006199
24	550001727	550001727	24	240006200	240006199
30/36	550001727	none	30/36	240006200	240006199

A toe kick kit is required when condensate pump is mounted below a floor-mounted air handler.

**Table 2** Toe kit option — part numbers

Air handler	Part number
09/12	550001785
24	550001786
30/36	550001787


Required when condensate pump is mounted below a floor-mounted air handler.

**Table 3** Discharge air speed and flow @ 230 VAC / Sound values

Model	High speed CFM (l/s)	Low speed CFM (l/s)	Coil	FPM (m/s)	Throw feet (m)	Observed sound values (dBA)
09-12	425 (200)	375 (175)	Dry	900 (4.6)	15 (4.6)	51
18-24	700 (350)	550 (250)	Dry	1,225 (6.2)	24 (7.3)	56
30/36	1,000 (470)	825 (400)	Dry	1,250 (6.4)	27 (8.2)	50

**UNCG/UNHG Air Handlers — Product Description** *(continued)*

**Figure 1** UNCG/UNHG ductless air handlers — dimensions, openings and knockouts



DIMENSIONS inches (mm)			
Model	A	B	C
UNHG09 UNHG12	26" (660)	11" (279)	41 1/2" (1054)
UNHG24	26" (660)	11" (279)	51 1/2" (1308)
UNCG30	27 1/2" (699)	12 3/8" (314)	62" (1575)
Model	D	E	F
UNHG09 UNHG12	5 1/2" (140)	35" (887)	19 3/16" (487)
UNHG24	5 1/2" (140)	45" (1141)	19 3/16" (487)
UNCG30	5 1/16" (141)	55 7/16" (1408)	20 23/32" (526)
Model	G	H	J
UNHG09 UNHG12	2 1/2" (64)	10 7/16" (265)	40 1/2" (1029)
UNHG24	2 1/2" (64)	10 7/16" (265)	50 1/2" (1283)
UNCG30 UNCG36	2 1/2" (64)	11 13/16" (300)	61" (1549)

- 1 Optional condensate pump floor-mount location (requires floor mount trim kit)
- 2 Supply and return air flow directions
- 3 Minimum clearance for air flow and access — BOTH sides of cabinet
- 4 Minimum clearance — ensure minimum clearance of 36 inches (914 mm) above supply air outlet and in front of return air inlet for air flow and access
- 5 Clearance holes (4) for securing unit to wall or ceiling, using appropriate hardware — 11/16 inch diameter
- 6 Knockout, 3-inch (76 mm), for optional customer-supplied/installed fresh air intake device
- 7 15/8 x 3 3/8 inches knockout each side of rear panel for refrigeration tubing, condensate drainage and/or power
- 8 Opening, 7/8 x 7/8 inch, on bottom right front corner of cabinet — for condensate drain tube routing when unit is ceiling mounted
- 9 Refrigeration and condensate draining connections are located in this area
- 10 Electrical connections are located in this area
- 11 Location of item 7, above
- 12 15/8 x 3 3/8 inches knockout each side panel for refrigeration tubing, condensate drainage and/or power
- 13 15/8 x 3 3/8 inches knockout at bottom left front for refrigeration tubing, condensate drainage and/or power, most often used when unit is ceiling mounted; pump kit riser flanges do not interfere with knockouts
- 14 15/8 x 3 3/8 inches knockouts at bottom left rear each side for refrigeration tubing, condensate drainage and/or power; pump kit riser flanges do not interfere with knockouts
- 15 15/8 x 3 3/8 inches knockout at bottom right front for refrigeration tubing, condensate drainage and/or power, most often used when unit is ceiling mounted; pump kit riser flanges do not interfere with knockouts
- 16 Optional floor mount trim kit — with 1-inch bottom flange; recessed 1/2 inch on front and sides, flush at rear
- 17 Distance from side of cabinet to 7/8 x 7/8 inch opening

**UNCG/UNHG Air Handlers with S1CG/S1HG/S2CG/S2HG Condensers**

**S1CG/S1HG/S2CG/S2HG — description**

The S1CG/S1HG and S2CG/S2HG condensing units are air-cooled, vertically-arranged side-discharge, high-efficiency units designed specifically to meet or exceed a 13 SEER rating.

- The S1CG Models 9,000-36,000 Btuh and S1HG Models 9,000-24,000 Btuh condensing units will provide cooling and heating for a single evaporator.
- The S2CG/S2HG 18,000 (99), 21,000 (92) and 24,000 (22) Btuh capacity condensing units will provide cooling and heating for two evaporators.
- The S1CG/S1HG, S2CG/S2HG are quiet units that can be recommended for both commercial and residential applications.

**NOTICE**

When specifying heat pump(s), it is recommended that the matching indoor unit(s) be equipped with electric heat.

**Features**

- Installation of the S1CG/S1HG and S2CG/S2HG condensing units is simplified by a 24v control interconnection from the evaporator.
- Multiple units can be lined up in close proximity to an exterior wall.
- Service valves are recessed to reduce tampering.
- All 9,000–12,000 Btuh units are equipped with an oversized suction accumulator with surge baffles and enhanced oil management and a factory-installed solid core filter drier.
- A factory-installed crankcase heater is standard on S1HG 9,000-12,000 Btuh (thermostatically-controlled) and S2HG models, and is available as optional equipment on other models.

**Controls and components (Factory-installed or supplied)**

- Compressor and fan motor contactor
- Run capacitor
- Low voltage terminal connections
- High pressure switch with manual external reset
- Heat pump hard start
- Cooling operation down to 60° F (15.6° C) standard on all units
- Models 9,000-12,000 Btuh only:
  - Large capacity suction accumulator
  - Solid-core filter drier

**Thermostatically-controlled crankcase heater**

- This feature energizes the crankcase heater only when needed, saving unnecessary power usage and increasing overall system efficiency.

**System options**

- Corrosion-resistant coil options (sea coast and harsh environment usage):
  - Copper fin/copper tube condenser coil
  - Coated aluminum fin/copper tube condenser coil
- Low Ambient controls for cooling operation down to 0° F (-18° C)
  - Optional field-installed kits, when specified, for cooling operation down to 0°F, S2HG cooling operation only available down to 32°F(0°C) — kits include louvers/wind baffle, crankcase heater, and/or fan cycle switch, and installation instructions
- Models S1CG 9,000-12,000 Btuh only:
  - 115v (single-zone only — S1CG or S1HG)
  - Field-installed thermostatically-controlled crankcase heater for heat


pump units (S1HG or S2CG)

**Installer-supplied items**

- Power wiring.
- Low-voltage wiring (18 AWG minimum).
- Secure mounting pad or foundation.
- Refrigerant piping (if not purchased from EMI).
- High-voltage disconnect.
- Refrigerant for charging interconnect piping.

**Table 4** Dimensional data, sound data and shipping weights

Model	Size Btu	Unit dimensions Inches (mm)			Sound level dBA	Shipping weight Lbs (kg)
		A	B	C		
S1CG/S1HG9	9,000	24 (610)	15 (381)	36 (914)	59	98 (44.5)
S1CG/S1HG2	12,000	24 (610)	15 (381)	36 (914)	59	98 (44.5)
S1CG/S1HG8	18,000	32 (813)	15 (381)	36 (914)	62	156 (70.9)
S1CG/S1HG4	24,000	32 (813)	15 (381)	40 (1016)	63	156 (70.9)
S1CG3	30,000	38 (965)	15 (381)	44 (1118)	68	210 (95.5)
S2CG	18,000/21,000/24,000	38 (965)	15 (381)	44 (1118)	68	197 (89.6)
S2HG	18,000/21,000/24,000	38 (965)	15 (381)	44 (1118)	68	197 (89.6)
S1CG6	36,000	38 (965)	15 (381)	48 (1219)	68	210 (95.5)




**Table 5** Cooling Operational Ranges

Unit	Voltage	Accessories Part Numbers (Quantity) Required *** Order ALL Kits Listed Under the Operational Range ***			
		Operational Range			
		32° to 115° F (0 to 46° C)	0° to 115° F (-18 to 46° C)		
		Crankcase Heater Kit	Crankcase Heater Kit	Fan Cycle Switch Kit	Architectural Louver/Hail Guard/Wind Baffle Kit
S1CG9000	115	550002072 (1)	550002072 (1)	550002074 (1)	550001577 (1)
S1CG2000	208/230	550002073 (1)	550002073 (1)	550002074 (1)	550001577 (1)
S1CG8000	208/230	N/R	N/R	550002074 (1)	550001578 (1)
S1CG4000	208/230	N/R	N/R	550002074 (1)	550001602 (1)
S1CG3000	208/230	N/R	N/R	550002074 (1)	550001580 (1)
S2CG	208/230	550002073 (2)	550002073 (2)	550002074 (2)	550001580 (1)
S2HG	208/230	N/R	N/R	N/R	550001580 (1)
S1CG6000	208/230	N/R	N/R	550002074 (1)	550001581 (1)
S1HG9000	115	N/R	N/R	550002074 (1)	550001577 (1)
S1HG2000	208/230	N/R	N/R	550002074 (1)	550001577 (1)
S1HG8000	208/230	N/R	N/R	550002074 (1)	550001578 (1)
S1HG4000	208/230	N/R	N/R	550002074 (1)	550001602 (1)

Note: N/R - Not Required



**UNCG/UNHG Air Handlers with S1CG/S1HG/S2CH/S2HH Condensers** (continued)



**Table 6** Performance — cooling system with universal units

Condenser	Universal Units	Btuh (Kw)	SEER	SHR	EER	Ref.
S1CG9000	UNHG09	9,000 (2.6)	13.0	0.74	12.2	R-410A
S1CG2000	UNHG12	12,000 (3.5)	13.0	0.68	11.9	R-410A
S1CG8000	UNHG24	18,000 (5.3)	13.0	0.77	12.0	R-410A
S1CG4000	UNHG24	23,800 (7.0)	13.0	0.67	11.4	R-410A
S1CG3000	UNCG30	28,200 (8.1)	13.0	0.79	11.7	R-410A
S1CG6000	UNCG36	33,600 (9.8)	13	0.69	11.6	R-410A
S2CH9900	UNHG09 + UNHG09	18,000 (5.3)	13.0	0.73	12.1	R-410A
S2CH9200	UNHG09 + UNHG12	21,000 (6.2)	13.0	0.70	12.0	R-410A
S2CH2200	UNHG12 + UNHG12	24,000 (7.0)	13.0	0.68	12.0	R-410A


**Table 7** Performance — heat pump system with universal units

Condenser	Universal Units	Cooling Btuh (Kw)	Heating Btuh (Kw)	SEER	HSPF	SHR	EER	COP	Ref.
S1HG9000	UNHG09	9,000 (2.6)	8,800 (2.6)	13.0	7.7	0.72	12.2	3.3	R-410A
S1HG2000	UNHG12	12,000 (3.5)	10,600 (3.1)	13.0	7.7	0.67	11.7	3.3	R-410A
S1HG8000	UNHG24	18,000 (5.3)	17,600 (5.2)	13.0	7.7	0.77	12.1	3.5	R-410A
S1HG4000	UNHG24	23,800 (7.0)	20,600 (6.0)	13.0	7.7	0.67	11.7	3.4	R-410A
S2HH9900	UNHG09 + UNHG09	18,000 (5.3)	17,400 (5.1)	13.0	7.7	0.73	12.1	3.2	R-410A
S2HH9200	UNHG09 + UNHG12	21,000 (6.2)	19,200 (5.6)	13.0	7.7	0.70	12.0	3.2	R-410A
S2HH2200	UNHG12 + UNHG12	24,000 (7.0)	21,000 (6.2)	13.0	7.7	0.68	12.0	3.2	R-410A

**Table 8** UNCG/UNHG interconnecting line sizes

Capacity	Max. Equivalent Length	Max. Lift	Max. Trap Height	Liquid Line	Suction Line	Condensate Line
		"H"	"P"	O.D.	O.D.	I.D.
9,000	50' (15 m)	20' (6 m)	15' (5 m)	1/4"	1/2"	1/2"
12,000				1/4"	1/2"	1/2"
18,000	100' (30 m)	35' (11 m)	20' (6 m)	3/8"	5/8" *	1/2"
24,000				3/8"	3/4"	1/2"
30,000				3/8"	3/4"	1/2"
36,000				3/8"	3/4"	1/2"

\* Must bush down to 5/8" interconnect for 18K system



**UNCG/UNHG Air Handlers with T2CG, T3CG or T4CG Condensers**

**T2CG, T3CG or T4CG — description**

EMI offers the finest 13 SEER high capacity multi-zone outdoor unit in the ductless split market. These top-discharge high-capacity condensing units allow the installation of up to four circuits from a single outside location when space or aesthetic requirements limit the use of locations. Each zone is independent and no mixing of refrigerant is required.

**Features**

- Compressors — Hermetically-sealed high-efficiency rotary or reciprocating types, depending on zone capacity. Motors are PSC type with inherent overload protection. Compressors are installed on resilient mountings.
- All 9,000-12,000 Btuh circuits are equipped with a Duratec Performance Package that includes an oversized suction accumulator with surge baffles and enhanced oil management and a factory-installed solid core filter drier.
- Cabinet - Fabricated of G90U galvaneal steel, finished with corrosion inhibiting, polyester, powder coated paint (2,000 hr. salt spray tested). Fan Guard — Black vinyl coated. Cabinet Color — Light gray & black.
- Refrigeration Circuit — The T2C, T3C, and T4C are delivered with pre-charged refrigerant (R410A) for the condenser coils and air handlers. Charging of the field-installed piping is required. Unit refrigeration valves are solid brass, for sweat connection. Solid core filter driers are factory installed on all models with rotary compressors.
- Condenser Coil — The condenser coils are tested to 600 psig and are constructed of seamless copper tubing, arranged in staggered configuration, with enhanced aluminum fins. The tubes are mechanically expanded for secure bonding to fin shoulder.
- Condenser Fan/Motor — The condenser fan is a large diameter, high efficiency, three or four blade (depending on capacity) aluminum propeller type, directly connected to the totally enclosed, PSC motor. The motor is fitted with internal thermal protection. These multi-zone units are a draw-through air flow design.

**Controls and components (Factory-installed or supplied)**


- Compressor and fan motor contactor
- Run capacitor
- Low voltage terminal connections
- High pressure switch with manual external reset
- Cooling operation down to 60° F (15.6° C) standard on all units
- Models with 9,000-12,000 Btuh circuits only:
  - Large capacity suction accumulator
  - Solid-core filter drier

**System options**

- Corrosion-resistant coil options (sea coast and harsh environment usage):
  - Copper fin/copper tube condenser coil.
  - Coated aluminum fin/copper tube condenser coil.
- Low Ambient controls for cooling operation down to 0° F (-18°C) (standard equipment can operate down to 32°F(0°F))
  - Optional field-installed kit, when specified, for cooling operation down to 0°F(-18°C) — kit includes control, louvers and wind baffle plus installation instructions.
  - Low Ambient controls for operation down to 0° F(-18°C) (consult factory for availability)
- Hard-start assist.

**Installer-supplied items**

- Power wiring.
- Low-voltage wiring (18 awg minimum).
- Secure mounting pad or foundation.
- Refrigerant piping (if not purchased from EMI).
- High-voltage disconnect.
- Refrigerant for charging interconnect piping.



**Table 9** Dimensional data, sound data and shipping weights

Model	Size	Sound level dBA	Shipping weight	
			Lbs	kg
T2CG	2400	70	325	147
T2CG	4400	70	325	147
T2CG	8800	70	325	147
T2CG	9800	70	325	147
T3CG	2240	70	325	147
T3CG	9980	70	325	147
T3CG	9990, 2220, 9920	70	325	147
T4CG	2222, 9922, 9992, 9999	70	325	147

**Table 10** Operational Ranges

Unit	Size	Accessories Part Numbers (Quantity) Required *** Order ALL Kits Listed Under the Operational Range ***			
		Operational Range			
		32° to 115° F (0 to 46° C)	0° to 115° F (-18 to 46° C)		
		Crankcase Heater Kit	Crankcase Heater Kit	Fan Cycle Switch Kit	Architectural Louver/Hail Guard/Wind Baffle Kit
T2CG*	2400, 9800	550002073 (1)	550002073 (1)	550002074 (2)	550002057
T2CG	4400, 8800	N/R	N/R	550002074 (2)	550002057
T3CG*	2240, 9980	550002073 (2)	550002073 (2)	550002074 (3)	550002057
T3CG	9990, 2220, 9920	550002073 (3)	550002073 (3)	550002074 (3)	550002057
T4CG	2222, 9922, 9992, 9999	550002073 (4)	550002073 (4)	550002074 (4)	550002057

Note: N/R - Not Required

\*Crankcase heater kits needed for 9,000-12,000 Btuh circuits only.

# UNCG/UNHG

High Efficiency Ductless Split System Universal Air Handler  
with EMI condensers

**EMI**  *Ductless*

*Comfort Where It Counts.*

Straight cool / Heat pump nominal capacities			
<b>UNHG09</b>	<b>UNHG12</b>	<b>UNHG24</b>	Units
9,000	12,000	18,000-23,800	Btuh
2.6	3.5	5.3-7.0	kW
Straight cooling only — nominal capacity			
<b>UNCG30</b>		<b>UNCG36</b>	Units
28,200		33,600	Btuh
8.3		9.8	kW

## Engineering Submittal

<b>Job Name:</b>
<b>Location:</b>
<b>Customer:</b>
<b>Project Engineer:</b>
<b>Project Architect:</b>
<b>General Contractor:</b>
<b>Submitted by:</b> For: Reference [ <input type="checkbox"/> ] Approval [ <input type="checkbox"/> ]
<b>Date:</b>

ECR International Inc  
2201 Dwyer Ave  
Utica, NY 13501  
www.enviromaster.com  
email: info@enviromaster.com



An ISO 9001-2008 Certified Company

### NOTICE

EMI air handlers and condensers are backed by EMI and ECR International and are tested, rated and certified in accordance with ARI Standard 210/240 and UL-1995. Due to ongoing product development, product designs and specifications may change without notice. Please contact the factory for more information.

Please fill in the  boxes below to specify the air handler units' codings

**Selection 1**

Quantity required:  **U** **N**  **G**

**Selection 2**

Quantity required:  **U** **N**  **G**

Type [ **UN** = universal air handler ]

Operation [ **C** = cooling—DX (UNCG 30 only) ]  
[ **H** = heat pump (UNHG 09–24 only) ]

Revision [ **G** = R-410A refrigerant ]

Capacity [ **09** = 9,000 Btuh ]  
[ **12** = 12,000 Btuh ]  
[ **24** = 18 / 24,000 Btuh ]  
[ **30** = 30 / 30,000 Btuh (cooling only) ]  
[ **36** = 36 / 36,000 Btuh (cooling only) ]

Auxiliary heat:

[ **0** = no auxiliary heat ]  
[ **3** = 3 kw @ 208/230 VAC, (UNHG 09, 12, 24 only)]  
[ **5** = 5 kw @ 208/230 VAC, ( UNHG 24, UNCG 30 only)]

Voltage [ **A** = 115 VAC (UNHG 09–12 only) ]  
[ **D** = 208/230 VAC ]

**EXAMPLES**

**U N C G 3 0 D 5**

Cooling application | 30 / 36,000 Btuh capacity  
| 208/230 VAC | 5 kw auxiliary heat

**U N H G 2 4 D 5**


Heat pump application | 18 / 24,000 Btuh capacity  
| 208/230 VAC | 5 kw auxiliary heat

Please check the boxes below to specify optional field-installed accessories

<input type="checkbox"/>	Condensate Pump	<input type="checkbox"/>	Metal return air grille
<input type="checkbox"/>	Remote thermostat for air handler	<input type="checkbox"/>	Floor mount trim kit (Required when condensate pump is mounted below a floor-mounted air handler)
<input type="checkbox"/>	Wind baffle / hail guard, architectural louver kit (required for cooling operation to 0°F (-18°C))	<input type="checkbox"/>	Refrigerant line set, 10-feet
<input type="checkbox"/>	Crankcase Heater (S1CG 9,000 - 12,000 Btuh only) required for cooling operating below 60°F (15°C)	<input type="checkbox"/>	Refrigerant line set, 25-feet
<input type="checkbox"/>	Hard Start Kit	<input type="checkbox"/>	Refrigerant line set, 50-feet
<input type="checkbox"/>	Fan Cycle Switch (required for cooling operation below 32°F (0°C))		



Please fill in the  boxes below to specify the condenser unit coding



Capacity code Individual zone capacity		Available Units					
Code	Capacity Btuh	( S ) Capacity codes	Description (Max combined capacity = 24,000 Btuh)	( T ) Capacity code	Description (Maximum combined capacity = 48,000 Btuh)		
<b>0</b>	Empty zone	<b>9000</b>	One zone   9,000 Btuh	<b>2400</b>	Two zones   12,000 / 24,000 Btuh		
<b>9</b>	9,000	<b>2000</b>	One zone   12,000 Btuh	<b>4400</b>	Two zones   24,000 / 24,000 Btuh		
<b>2</b>	12,000	<b>8000</b>	One zone   18,000 Btuh	<b>8800</b>	Two zones   18,000 / 18,000 Btuh		
<b>8</b>	18,000	<b>4000</b>	One zone   24,000 Btuh	<b>9800</b>	Two zones   9,000 / 18,000 Btuh		
<b>4</b>	24,000	<b>3000 *</b>	One zone   30,000 Btuh	<b>2220</b>	Three zones   12,000 / 12,000 / 12,000 Btuh		
<b>3</b>	30,000 *	<b>6000 *</b>	One zone   36,000 Btuh	<b>2240</b>	Three zones   12,000 / 12,000 / 24,000 Btuh		
<b>6</b>	36,000 *	<b>9900</b>	Two zones   9,000 / 9,000 Btuh	<b>9920</b>	Three zones   9,000 / 9,000 / 12,000 Btuh		
* Straight cooling units ONLY		<b>9200</b>	Two zones   9,000 / 12,000 Btuh	<b>9980</b>	Three zones   9,000 / 9,000 / 18,000 Btuh		
<b>Max total capacity</b> Multi-zone units		<b>2200</b>	Two zones   12,000 / 12,000 Btuh	<b>9990</b>	Three zones   9,000 / 9,000 / 9,000 Btuh		
( S ) 2 zones 24,000 Btuh max total		* Available in straight cooling units ONLY					
( T ) 4 zones 48,000 Btuh max total							
						<b>9999</b>	Four zones   9,000 / 9,000 / 9,000 / 9,000 Btuh
						<b>9992</b>	Four zones   9,000 / 9,000 / 9,000 / 12,000 Btuh
		<b>9922</b>	Four zones   9,000 / 9,000 / 12,000 / 12,000 Btuh				
		<b>2222</b>	Four zones   12,000 / 12,000 / 12,000 / 12,000 Btuh				

**EXAMPLES**


<b>S</b>	<b>1</b>	<b>C</b>	<b>G</b>	<b>8</b>	<b>0</b>	<b>0</b>	<b>0</b>	<b>D</b>	<b>0</b>	<b>1</b>	<b>T</b>	<b>2</b>	<b>H</b>	<b>G</b>	<b>9</b>	<b>8</b>	<b>0</b>	<b>0</b>	<b>D</b>	<b>1</b>	<b>2</b>
Side discharge   one zone   cooling only   rev. G   18,000 Btuh   208/230 V   standard low volt control   copper fin, copper coil											Top discharge   two zones   heat pump   rev. G   9,000 / 18,000 Btuh   208/230 V   32°F Low ambient control   coated exchanger										
<b>S</b>	<b>2</b>	<b>H</b>	<b>G</b>	<b>9</b>	<b>2</b>	<b>0</b>	<b>0</b>	<b>D</b>	<b>1</b>	<b>0</b>	<b>T</b>	<b>4</b>	<b>C</b>	<b>G</b>	<b>9</b>	<b>9</b>	<b>2</b>	<b>2</b>	<b>D</b>	<b>0</b>	<b>0</b>
Side discharge   two zones   heat pump   rev. G   9,000 / 12,000 Btuh   208/230 V   32°F Low ambient control   aluminum fin, copper coil											Top discharge   four zones   cooling only   rev. G   9,000 / 9,000 / 12,000 / 12,000 Btuh   208/230 V   standard low volt control   aluminum fin, copper coil										

ECR International Inc  
2201 Dwyer Ave  
Utica, NY 13501  
[www.enviromaster.com](http://www.enviromaster.com)  
email: [info@enviromaster.com](mailto:info@enviromaster.com)



*An ISO 9001-2008 Certified Company*

**UNCG/UNHG Air Handlers with T2CG, T3CG or T4CG Condensers (continued)**




**Table 13** System options with T2C, T3C or T4C top discharge

Condenser	Air Handlers	Btuh	SEER	SHR	EER	Ref.
T2CG2400	UNHG12 UNHG24	35,800	13.0	0.69	11.5	410A
T2CG4400	(2) UNHG24	47,600	13.0	0.67	11.5	410A
T2CG9800	UNHG09 UNHG24	27,000	13.0	0.76	11.5	410A
T2CG8800	(2) UNHG24	36,000	13.0	0.74	11.5	410A
T3CG2220	(3) UNHG12	36,000	13.0	0.72	11.5	410A
T3CG2240	(2) UNHG12 UNHG24	47,800	13.0	0.71	11.5	410A
T3CG9920	(2) UNHG09 UNHG12	30,000	13.0	0.76	11.5	410A
T3CG9980	(2) UNHG09 UNHG24	36,000	13.0	0.76	11.5	410A
T3CG9990	(3) UNHG09	27,000	13.0	0.78	11.5	410A
T4CG2222	(4) UNHG12	48,000	13.0	0.72	11.5	410A
T4CG9922	(2) UNHG09 (2) UNHG12	42,000	13.0	0.74	11.5	410A
T4CG9992	(3) UNHG09 UNHG12	39,000	13.0	0.76	11.5	410A
T4CG9999	(4) UNHG09	36,000	13	0.78	11.5	R410A

**Table 14** UNCG/UNHG interconnecting line sizes

Capacity	Max. Equivalent Length	Max. Lift	Max. Trap Height	Liquid Line	Suction Line	Condensate Line
		"H"	"P"	O.D.	O.D.	I.D.
9,000	50' (15 m)	20' (6 m)	15' (5 m)	1/4"	1/2"	1/2"
12,000				1/4"	1/2"	1/2"
18,000	100' (30 m)	35' (11 m)	20' (6 m)	3/8"	5/8" *	1/2"
24,000				3/8"	3/4"	1/2"
30,000				3/8"	3/4"	1/2"

\* Must bush down to 5/8" interconnect for 18K system



**UNCG/UNHG Air Handlers with T2HG, T3HG or T4HG Condensers**

**T2HG, T3HG or T4HG — description**

EMI offers the finest multi-zone heat pump outdoor units in the ductless split market, the T series (T2HB, T3HB & T4HB) condensing units. These units allow the installation of two or more circuits from a single outside location, ideal for when space or aesthetic requirements limit the use of the number of cabinets outdoors. Each zone is independent so no mixing of refrigerant occurs.

**NOTICE**

When specifying heat pump(s), it is recommended that the matching indoor unit(s) be equipped with electric heat.

**Features**

- Compressors — Hermetically-sealed high-efficiency rotary or reciprocating types, depending on zone loads. Motors are PSC type with inherent overload protection. Compressors are installed on resilient mountings.
- All 9,000-12,000 Btuh units are equipped with a Duratec Performance Package that includes an oversized suction accumulator with surge baffles and enhanced oil management and a factory-installed solid core filter drier.
- Cabinet - Fabricated of G90U galvaneal steel, finished with corrosion inhibiting, polyester, powder coated paint (2,000 hr. salt spray tested). Fan Guard — Black vinyl coated. Cabinet Color — Light gray & black.
- Refrigeration Circuit — The T2C, T3C, and T4C are delivered with pre-charged refrigerant (R410A) for the condenser coils and evaporators. Charging of the field-installed piping is required. Unit refrigeration valves are solid brass, for sweat connection. Solid core filter driers are factory installed on all models with rotary compressors.
- Condenser Coil — The condenser coils are tested to 600 psig and are constructed of seamless copper tubing, arranged in staggered configuration, with enhanced aluminum fins. The tubes are mechanically expanded for secure bonding to fin shoulder.
- Condenser Fan/Motor — The condenser fan is a large diameter, high efficiency, three or four blade (depending on capacity) aluminum propeller type, directly connected to the totally enclosed, PSC motor. The motor is fitted with internal thermal protection. These multi-zone units are a draw-through air flow design.
- All 18,000 and 24,000 Btuh circuit units include a solid core filter drier and high pressure limit switch. The 18,000 Btuh circuits also include a large capacity suction accumulator with surge baffles and enhanced oil management.

**Controls and components (factory installed and supplied)**

- Compressor and fan motor contactor
- Run capacitor
- Low voltage terminal connections
- High pressure switch with manual external reset
- Heat pump hard start
- Cooling operation down to 32°F (0°C) standard on all units
- Cooling operation only available down to 32°F (0°C)
- Models 9,000-12,000 Btuh only:
  - Large capacity suction accumulator
  - Solid-core filter drier

**Thermostatically-controlled crankcase heater**


- This feature energizes the crankcase heater only when needed, saving unnecessary power usage and increasing overall system efficiency.

**System options**

- Corrosion-resistant coil options (sea coast and harsh environment usage):
  - Copper fin/copper tube condenser coil.
  - Coated aluminum fin/copper tube condenser coil.
- Wind baffles — louvers.

**Installer-supplied items**

- Power wiring.
- Low-voltage wiring (18 awg minimum).
- Secure mounting pad or foundation.
- Refrigerant piping (if not purchased from EMI).
- High-voltage disconnect.
- Refrigerant for charging interconnect piping.



**Table 15** Dimensional data, sound data and shipping weights

Model	Size	Sound level dBA	Shipping weight	
			Lbs	kg
T2HG	2400	70	325	147
T2HG	4400	70	325	147
T2HG	8800	70	325	147
T2HG	9800	70	325	147
T3HG	2240	70	325	147
T3HG	9980	70	325	147
T3HG	9990, 2220, 9920	70	325	147
T4HG	2222, 9922, 9992, 9999	70	325	147


**Table 16** Cooling Operational Ranges

Unit	Size	Accessories Part Numbers (Quantity) Required *** Order ALL Kits Listed Under the Operational Range ***			
		Operational Range			
		32° to 115° F (0 to 46° C)	0° to 115° F (-18 to 46° C)		Architectural Louver/Hail Guard/Wind Baffle Kit
Crankcase Heater Kit	Crankcase Heater Kit	Fan Cycle Switch Kit			
T2HG	2400, 9800	N/R	N/R	N/R	550002057
T2HG	4400, 8800	N/R	N/R	N/R	550002057
T3HG	2240, 9980	N/R	N/R	N/R	550002057
T3HG	9990, 2220, 9920	N/R	N/R	N/R	550002057
T4CG	2222, 9922, 9992, 9999	N/R	N/R	N/R	550002057

Note: N/R - Not Required



**UNCG/UNHG Air Handlers with T2HG, T3HG or T4HG Condensers**




**Table 17** System options with T2H, T3H or T4H top discharge

Condenser	Wall unit	Cooling Btuh	Heating Btuh	SEER	HSPF	SHR	EER	COP	Ref.
T2HG2400	UNHG12 UNHG24	35,800	32,400	13.0	7.7	0.69	11.5	3.2	410A
T2HG4400	(2) UNHG24	47,500	44,000	13.0	7.7	0.67	11.5	3.1	410A
T2HG9800	UNHG09 UNHG24	27,000	25,000	13.0	7.7	0.76	11.5	3.4	410A
T2HG8800	(2) UNHG24	36,000	33,000	13.0	7.7	0.74	11.5	3.4	410A
T3HG2220	(3) UNHG12	36,000	31,200	13.0	7.7	0.72	11.5	3.1	410A
T3HG2240	(2) UNHG12 UNHG24	47,500	42,800	13.0	7.7	0.71	11.5	3.1	410A
T3HG9920	(2) UNHG09 UNHG12	30,000	27,400	13.0	7.7	0.76	11.5	3.3	410A
T3HG9980	(2) UNHG09 UNHG24	36,000	33,500	13.0	7.7	0.76	11.5	3.4	410A
T3HG9990	(3) UNHG09	27,000	25,500	13.0	7.7	0.78	11.5	3.5	410A
T4HG2222	(4) UNHG12	48,000	41,500	13.0	7.7	0.72	11.5	3.1	410A
T4HG9922	(2) UNHG09 (2) UNHG12	42,000	37,800	13.0	7.7	0.74	11.5	3.2	410A
T4HG9992	(3) UNHG09 UNHG12	39,000	35,900	13.0	7.7	0.76	11.5	3.4	410A
T4HG9999	(4) UNHG09	36,000	34,000	13.0	7.7	0.78	11.5	3.5	410A

**Table 18** UNCG/UNHG interconnecting line sizes

Capacity	Max. Equivalent Length	Max. Lift	Max. Trap Height	Liquid Line	Suction Line	Condensate Line
		"H"	"P"	O.D.	O.D.	I.D.
9,000	50' (15 m)	20' (6 m)	15' (5 m)	1/4"	1/2"	1/2"
12,000				1/4"	1/2"	1/2"
18,000	100' (30 m)	35' (11 m)	20' (6 m)	3/8"	5/8" *	1/2"
24,000				3/8"	3/4"	1/2"
30,000				3/8"	3/4"	1/2"

\* Must bush down to 5/8" interconnect for 18K system



## Electrical Specifications

### NOTICE

Due to ongoing product development, designs, specifications, and performance are subject to change without notice. Please consult the factory for further information.

**Table 19** Electrical specifications — UNCG/UNHG

MODEL	VOLTS/HZ/PH	FAN RLA	HP	HEATER K.W.	AMPS	TOTAL AMPS	MIN VOLT	M.C.A.	HACR BRKR
<b>UNHG 09-12</b>	115/60/1	0.64	0.02	–	–	0.64	104	0.8	15
	208/230/60/1	0.34	0.02	–	–	0.34	197	0.4	15
	208/230/60/1	0.34	0.02	3	13.04	13.38	197	16.7	20
<b>UNHG 24</b>	208/230/60/1	0.56	0.07	–	–	0.56	197	0.7	15
	208/230/60/1	0.56	0.07	3	13.04	13.6	197	17	20
	208/230/60/1	0.56	0.07	5	21.74	22.3	197	27.9	30
<b>UNCG 30/36</b>	208/230/60/1	0.8	0.10	–	–	0.8	197	1	15
	208/230/60/1	0.8	0.10	5	21.74	22.54	197	28.2	30

**Table 20** Electrical specifications — S1CG/S1HG,S2CG/S2HG

Model #	Volts/HZ/PH	Fan Motor		Compressor				Total amps	Min volt	M.C.A.	HACR BRKR
		AMPS	HP	Circuit 1		Circuit 2					
				RLA	LRA	RLA	LRA				
S1CG9000A S1HG9000A	115/60/1	1.4	0.125	7.5	47	N/A		8.9	104	10.8	15
S1CG2000A S1HG2000A	115/60/1	1.4	0.125	9.9	53	N/A		11.3	104	13.8	20
S1CG9000D S1HG9000D	208/230/60/1	0.8	0.125	3.9	20	N/A		4.7	197	5.7	15
S1CG2000D S1HG2000D	208/230/60/1	0.8	0.125	5.2	27	N/A		6.0	197	7.3	15
S1CG8000D S1HG8000D	208/230/60/1	0.8	0.125	5.9	43	N/A		6.7	197	8.2	15
S1CG4000D S1HG4000D	208/230/60/1	0.8	0.125	8.0	43	N/A		8.8	197	10.8	15
S1CG3000D	208/230/60/1	1.8	0.330	11.6	74	N/A		13.4	197	16.3	25
S1CG6000D	208/230/60/1	1.8	0.330	11.5	79	N/A		13.3	197	16.2	25
S2CH2200D S2HH2200D	208/230/60/1	0.8	0.330	5.2	27	5.2	27	11.2	197	12.5	15
S2CH9200D S2HH9200D	208/230/60/1	0.8	0.330	3.9	20	5.2	27	9.9	197	11.2	15
S2CH9900D S2HH9900D	208/230/60/1	0.8	0.330	3.9	20	3.9	20	8.6	197	9.6	15

M.C.A. - minimum circuit amps

**Electrical Specifications (cont.)**

**Table 21** Electrical specifications — T2CG/T3CG/T4CG, T2HG/T3HG/T4HG

Model #	Volts/HZ/PH	Fan Motor		Compressor Zone-1		Compressor Zone-2		Compressor Zone-3		Compressor Zone-4		Total amps	Min volt	M.C.A.	HACR BRKR
		AMPS	HP	RLA	LRA	RLA	LRA	RLA	LRA	RLA	LRA				
T2CG2400D	208/230/60/1	1.8	0.33	5.2	27	8.2	58.3					15.2		17.3	25
T2CG4400D	208/230/60/1	1.8	0.33	8.2	58.3	8.2	58.3					18.2	197	20.3	25
T2CG8800D	208/230/60/1	1.8	0.33	5.9	43	5.9	43					13.6	197	15.1	20
T2CG9800D	208/230/60/1	1.8	0.33	3.9	20	5.9	43					11.6	197	13.1	15
T3CG2220D	208/230/60/1	1.8	0.33	5.2	27	5.2	27	5.2	27			17.4	197	18.7	20
T3CG2240D	208/230/60/1	1.8	0.33	5.2	27	5.2	27	8.2	58.3			20.4	197	22.5	30
T3CG9920D	208/230/60/1	1.8	0.33	3.9	20	3.9	20	5.2	27			14.8	197	16.1	20
T3CG9990D	208/230/60/1	1.8	0.33	3.9	20	3.9	20	3.9	20			13.5	197	14.5	15
T3CG9980D	208/230/60/1	1.8	0.33	3.9	20	3.9	20	5.9	43			15.5	197	17	20
T4CG2222D	208/230/60/1	1.8	0.33	5.2	27	5.2	27	5.2	27	5.2	27	22.6	197	23.9	25
T4CG9922D	208/230/60/1	1.8	0.33	3.9	20	3.9	20	5.2	27	5.2	27	20	197	21.3	25
T4CG9992D	208/230/60/1	1.8	0.33	3.9	20	3.9	20	3.9	20	5.2	27	18.7	197	20	25
T4CG9999D	208/230/60/1	1.8	0.33	3.9	20	3.9	20	3.9	20	3.9	20	17.4	197	18.4	20
T2HG2400D	208/230/60/1	1.8	0.33	5.2	27	8.2	58.3					15.2	197	17.3	25
T2HG4400D	208/230/60/1	1.8	0.33	8.2	58.3	8.2	58.3					18.2	197	20.3	25
T2HG8800D	208/230/60/1	1.8	0.33	5.9	43	5.9	43					13.6	197	15.1	20
T2HG9800D	208/230/60/1	1.8	0.33	3.9	20	5.9	43					11.6	197	13.1	15
T3HG2220D	208/230/60/1	1.8	0.33	5.2	27	5.2	27	5.2	27			17.4	197	18.7	20
T3HG2240D	208/230/60/1	1.8	0.33	5.2	27	5.2	27	8.2	58.3			20.4	197	22.5	30
T3HG9920D	208/230/60/1	1.8	0.33	3.9	20	3.9	20	5.2	27			14.8	197	16.1	20
T3HG9980D	208/230/60/1	1.8	0.33	3.9	20	3.9	20	5.9	43			15.5	197	17	20
T3HG9990D	208/230/60/1	1.8	0.33	3.9	20	3.9	20	3.9	20			13.5	197	14.5	15
T4HG2222D	208/230/60/1	1.8	0.33	5.2	27	5.2	27	5.2	27	5.2	27	22.6	197	23.9	25
T4HG9922D	208/230/60/1	1.8	0.33	3.9	20	3.9	20	5.2	27	5.2	27	20	197	21.3	25
T4HG9992D	208/230/60/1	1.8	0.33	3.9	20	3.9	20	3.9	20	5.2	27	18.7	197	20	25
T4HG9999D	208/230/60/1	1.8	0.33	3.9	20	3.9	20	3.9	20	3.9	20	17.4	197	18.4	20

M.C.A. - minimum circuit amps

**EMI's Product Line**

**Indoor Units**


**WLCG/WLHG**  
*High Wall Air Handler*



**CACG/CAHG**  
*Cassette Air Handler*




**UNCG/UNHG**  
*Universal Floor or Ceiling Air Handler*



**Outdoor Units**

**S2CG/S2HG Dual Zone**  
*Side Discharge*



**S1CG/S1HG**  
*Single Zone*  
*Side Discharge*

**T2CG/T2HG, T3CG/  
T3HG, and  
T4CG/T4HG 2, 3 and  
4 Zone**  
*Top Discharge*



ECR International Inc  
2201 Dwyer Ave  
Utica, NY 13501  
[www.enviromaster.com](http://www.enviromaster.com)  
email: [info@enviromaster.com](mailto:info@enviromaster.com)