



Comfort Where It Counts.


T2C, T3C, T4C & WLH SYSTEMS

Multi-Zone Cooling Only

Rev. 1.0 [7/06]

JOB NAME: _____ LOCATION: _____
 PURCHASER: _____
 ENGINEER: _____
 SUBMITTED TO: _____ FOR: REFERENCE [] APPROVAL [] CONSTRUCTION []
 SUBMITTED BY: _____ DATE: _____
 UNIT DESIGNATION: SCHEDULE #: _____ MODEL #: _____

WLH High Wall



T2C, T3C & T4C Top Discharge



EMI ENGINEERING SUBMITTAL

▲ CAPACITIES:

Indoor Design Temp °F
Cooling

DB/WB
80/67

Outdoor Design Temp °F
Cooling

DB/WB
95/75

WLC/WLH ELECTRICAL SPECIFICATIONS								
Model	Volts/HZ/ PH	Fan RLA	Heate K.W.	Amps	Total Amps	Min Volt	M.C.A.	HACR BRKR
SMALL CABINET 09/12								
WLHA 09/12	115/60/1	0.64	-	-	0.64	104	0.8	15
	115/60/1	0.64	0.75	6.5	7.14	104	8.9	15
	208/230/60/1	0.34	-	-	0.34	197	0.4	15
	208/230/60/1	0.34	3	13.04	13.38	197	16.7	20
MEDIUM CABINET 24								
WLHA 24	115/60/1	1.2	-	-	1.20	104	1.5	15
	115/60/1	1.2	0.75	6.52	7.72	104	9.7	15
	115/60/1	1.2	1.25	10.9	12.10	104	15.1	20
	208/230/60/1	0.56	-	-	0.56	197	0.7	15
	208/230/60/1	0.56	3	13.04	13.60	197	17.0	20
	208/230/60/1	0.56	5	21.74	22.30	197	27.9	30

OUTDOOR UNIT ELECTRICAL SPECS T2C, T3C, AND T4C 208/230V - 60 HERTZ 1 - PHASE						
Capacity	FAN MTR		Total Amps	MCA	HACR BRKR	Min Volt
	Amps	HP				
9999	1.8	0.33	15.8	16.7	20	197
2222	1.8	0.33	19.8	21.0	25	197
9222	1.8	0.33	18.8	19.9	20	197
9992	1.8	0.33	16.5	17.7	20	197
9922	1.8	0.33	17.8	19.0	20	197
8800	1.8	0.33	12.6	14.0	15	197
4400	1.8	0.33	17.8	19.8	25	197
9940	1.8	0.33	16.6	18.6	25	197
9990	1.8	0.33	12.0	12.9	15	197
2220	1.8	0.33	15.3	16.5	20	197
9800	1.8	0.33	10.6	12.0	15	197
8400	1.8	0.33	15.2	17.2	25	197
2400	1.8	0.33	14.3	16.3	20	197
9280	1.8	0.33	15.1	16.5	20	197
9240	1.8	0.33	17.7	19.7	25	197
2280	1.8	0.33	16.2	17.6	20	197
9220	1.8	0.33	14.2	15.4	20	197
9920	1.8	0.33	13.1	14.3	15	197
9980	1.8	0.33	14.0	15.4	20	197
2240	1.8	0.33	18.8	20.8	25	197



EMI ENGINEERING SUBMITTAL T2C, T3C, T4C & WLH

▲ STANDARD FEATURES:

Evaporator – High Wall Mounted:



- Universal unit mounted, infrared compatible control package, configurable to either unit mount or optional wall thermostat operation.
- Compatible with most standard wall mounted, 24V thermostats
- Motorized supply louver
- Integral field condensate pump connector
- Condensate pan over flow protection
- Anti-short cycle compressor protection
- Indoor coil freeze protection
- Dry mode for humidity control (*optional electric heat required*)
- Memory back up for auto re-start following power outage
- Fan purge

Condenser – Top Discharge::

- Compressor and fan motor contactor
- Capacitors (*compressor & motor*)
- Loss of charge switches – 9,000 & 12,000 Btuh w/rotary compressor
- Low Voltage (24V) connections
- High pressure control on 18,000 to 24,000 Btuh with reciprocating or scroll type compressor
- Large capacity suction accumulator (*9,000 & 12,000 Btuh zones with rotary compressors only*)
- Factory installed solid core filter driers (*9,000 & 12,000 Btuh zones with rotary compressors only*)

WLH DIMENSIONS AND SPECIFICATIONS

NOTE: Due to ongoing development programs, design and specifications may change without notice.



WLH PHYSICAL DIMENSIONS					
Model	"A" Depth	"B" Height	"C" Length	"D" Mounting Bracket Clearance	"E" Tubing Access Clearance
WLHA09	9 7/8"	15 1/4"	38 1/2"	24"	26 1/2"
WLHA12	9 7/8"	15 1/4"	38 1/2"	24"	26 1/2"
WLHA24	9 7/8"	15 1/4"	48 1/2"	34"	36 1/2"

WLH SHIPPING WEIGHT	
Model	Lbs.
WLHA09	58.00
WLHA12	60.25
WLHA24	66.20

WLH SOUND VALUES * (230V High Speed Fan)	
Model	dBA
9/12	45
18/24	56


WLH INTERCONNECTING-LINE SIZE IN O.D.		
System Capacity Btuh	Liquid	Suction
9,000	1/4"	1/2"
12,000	1/4"	1/2"
18,000	3/8"	5/8"
24,000	3/8"	3/4"

* WLH Suction Connection size is 3/4" O.D. and must bush down at the WLH Unit.

DISCHARGE AIR SPEED AND FLOW @ 230V					
Model	High CFM	Low CFM	Coil	FPM	Throw/Ft.
9/12	400	350	Dry	900	15
18/24	750	675	Dry	1,225	25

Condensor Shipping Weight	
Model	(Lbs.)
9999	265
2222	290
9922	280
9992	270
9222	285
8800	320
4400	325
9940	295
9990	250
2220	265
9800	275
8400	325
2400	285
9280	300
9240	305
2280	310
9220	260
9920	255
9980	295
2240	310

T2C, T3C & T4C SPECIFICATIONS AND DIMENSIONS



Cabinet Size	Dim. A	Dim. B	Dim. C
Small	41"	32"	26"
Large	41"	32"	30"

Piping Specification		
Refrigerant Line Size O.D.		
Model	Liquid	Suction
09, 12	1/4"	1/2"
18	3/8"	5/8"
24	3/8"	3/4"

Note: Do not up size or alter line sizes.

Sound Levels	
Model	dBA
09-12	70
18	70
24	70

▲ PART ONE "GENERAL"

The straight cool air conditioning systems shall be an EMI America Series multi-zone split system per the equipment schedule. The system shall consist of two or more indoor air handler models per the air handler equipment schedule and matching America Series multi-zone condenser per the condenser equipment schedule. The units shall be made within North America. The units shall be listed by Intertek Testing Service (ITS) and bear the ETL label. All wiring shall be in accordance with the National Electrical Code (N.E.C.). The units shall be rated in accordance with ARI Standard 210/240 and bear the ARI label. The units shall be manufactured in a facility certified to ISO 9001, which is an international standard used to provide guidance in the development and implementation of an effective Quality Management System. The condensing unit shall contain R-22 refrigerant charge for the evaporator section and condenser section. The system efficiency shall meet or exceed 2006 Federal Standards.

▲ PART TWO "WARRANTY"

The units shall have a manufacturer's warranty for a period of (1) year from date of installation. The compressors shall have a warranty of (5) years from date of installation. If, during this period, any part should fail to function properly due to defects in workmanship or material, it shall be replaced or repaired at the discretion of Enviromaster International LLC. This warranty does not include labor. Manufacturer shall have twenty years experience in the U.S. market.

▲ PART THREE "PERFORMANCE"

Each indoor unit, specified by the air handler equipment schedule, shall provide a total minimum capacity, SEER, and EER at ARI standard conditions per the chart below. The system net minimum total cooling capacity and circulating air rate at 80°F (DB)/67°F (WB) entering the indoor coil and 95°F (DB) air entering the outdoor coil for the circuit combinations on the equipment schedule shall be rated per the *System Performance Chart*. The total power consumption of the combined system listed on the equipment schedule shall not exceed the wattage listed.

HIGH WALL & TOP DISCHARGE						
SYSTEM PERFORMANCE	Indoor - WLH Unit	Total Capacity	System Watts	SEER	SHR	EER
	9 + 18	27,000	2288	13	.80	11.8
	18 + 18	36,000	2975	13	.79	12.1
	12 + 24	34,000	2881	13	.72	11.8
	18 + 24	41,000	3475	13	.76	11.8
	24 + 24	45,000	3813	13	.73	11.8
	9 + 9 + 9	27,000	2307	13	.80	11.7
	9 + 9 + 12	30,000	2608	13	.77	11.9
	9 + 12 + 12	32,000	2711	13	.74	11.8
	9 + 9 + 18	36,000	3050	13	.80	11.8
	12 + 12 + 12	34,000	2906	13	.71	11.7
	9 + 12 + 18	39,000	3362	13	.77	11.6
	9 + 9 + 24	41,000	3534	13	.77	11.6
	12 + 12 + 18	41,000	3474	13	.74	11.8
	9 + 12 + 24	43,000	3644	13	.75	11.8
	12 + 12 + 24	46,000	3931	13	.72	11.7
	9 + 9 + 9 + 9	36,000	3050	13	.80	11.8
	9 + 9 + 9 + 12	38,000	3220	13	.71	11.8
	9 + 9 + 12 + 12	41,000	3565	13	.73	11.9
9 + 12 + 12 + 12	42,000	3559	13	.71	11.8	
12 + 12 + 12 + 12	45,000	3846	13	.73	11.7	

▲ PART FOUR "INDOOR UNIT"

The indoor unit shall be factory assembled, wired and contain a low voltage transformer. The cabinet will be ABS plastic with a light gray finish and have a galvanized steel sub chassis. The evaporator fan shall be an assembly with line flow tangential fan direct driven by a single motor. The fan shall be statically and dynamically balanced and run on permanently lubricated bearings. Motorized louver shall be provided with the ability to change the airflow vertically.

Horizontal-manually adjustable discharge louvers will be provided that can be placed in a fixed position. Return air shall be filtered by means of a washable, reusable mesh filter. The evaporator coil shall be of nonferrous construction with louvered fins bonded to rifled copper tubing. The tubing shall have inner grooves for high efficiency heat exchange. All tube joints shall be brazed with phoscopper or silver alloy. The coil shall be pressure tested at the factory. A condensate management system with over flow protection, condensate drain pan with anti-corrosion coating and drain shall be provided under the coil. System refrigerant flow shall be controlled by means of an orifice piston in the indoor unit. The unit electrical power shall be 208/230 or 115 Volts, 1 phase, 60 Hertz. The indoor unit shall be capable of satisfactory operation within the voltage limits of 208/230 or 115 +/- 10% Volts.

▲ PART FIVE "CONTROL SYSTEM"

The control system shall consist of a universal unit mounted, infrared compatible control package, configurable to either unit mount or optional wall thermostat operation. Interconnected low voltage wiring shall run from indoor unit to outdoor unit direct, no splices. When running low voltage wiring a double insulated, 18 gage cable is mandatory or use shielded cable. The microprocessor shall be factory wired and located within the indoor unit. The control unit will have a large LCD backlit display and be configurable to either unit mount or remote wall thermostat operation. Unit mount-control operation allows the use of an optional IR hand held controller. The control shall have the capability of sensing return air temperature and indoor coil temperature. The operational range will have adjustable set points from 55°F to 90°F in one degree increments. The universal control can be used in cooling only, cooling with optional electric heat, heat pump or heat pump with optional second stage electric heat. Operation modes include, cool, heat, fan, auto change over and dry. Fan operation of auto (cycling), high and low (constant), auto fan operation automatically selects fan speed according to heating or cooling demand. Dry mode operates cooling and optional electric heat simultaneously to remove humidity (optional electric heat required). Test mode allows for ease of testing after installation (all timers are eliminated). Room air sampling (fan auto mode) cycles the fan on periodically to remove temperature stratification. Fan purge runs the indoor fan for 60 seconds after call is dropped for cool/heat, improving unit efficiency. Unit protection features include, anti short cycling compressor protection, minimum compressor run time, freeze protection to prevent evaporator freeze, filter change indicator, condensate pan overflow switch, and integral condensate pump safety-switch connection. With this feature the control monitors the condensate pump safety switch and displays an error code if a fault occurs. The unit shall also provide non-volatile back up memory, where control settings are maintained for an indefinite period during a power outage. When power is restored the equipment will resume operation after a 3 minute compressor time delay. The control voltage shall be 24V AC generated from the indoor units transformer.

▲ PART SIX "OUTDOOR UNIT"

The outdoor unit shall be completely factory assembled, piped and wired. The cabinet shall be fabricated of G90U galvalume steel, finished with corrosion inhibiting, polyester, powder coated paint (2,000 hr. salt spray tested), finished in light gray with a black vinyl coated fan guard. The unit shall be furnished with (1) large diameter, direct drive, high efficiency propeller type fan. The motor shall be PSC type with internal overload protection and shall be permanently lubricated and resiliently mounted for quiet operation. The fan shall be provided with a guard to prevent contact with moving parts. The 9/12 nominal compressors shall be of the high performance rotary type with Duratec package consisting of an oversized accumulators, factory installed solid core filter driers and thermal overloads. The 18/24 nominal compressors shall be high performance reciprocating or scroll type. The compressors shall be mounted as to avoid the transmission of vibration. The condenser shall have easy access hose connections at 45° from valve body. The refrigeration system shall be equipped with loss of charge switch or manual reset high pressure switch and have the capability to operate with a maximum height difference of 35 feet and overall refrigerant tubing length of 100 feet between indoor and outdoor sections without the need for line size changes of additional oil. Refrigerant circuits shall be independent and contain its own compressor, refrigerant piping, service valve, expansion device and evaporator. The condenser coil shall be U-shaped and protected by a wire coil guard. Coil construction is seamless copper tubing with enhanced aluminum fins. The tubes are mechanically expanded for secure bonding to the fin. The unit electrical power shall be 208/230V, 1 phase, 60 Hertz. The system shall be capable of operation within voltage limits of 208/230V +/- 10%.

▲ PART SEVEN "OPTIONAL EQUIPMENT"

- **Hand held infrared remote controller**
- **24 Volt remote wall thermostat**
- **3KW or 5KW electric heat** with automatic reset high temperature cutout and redundant high temperature fuse link
- **Low ambient** control field installed for cooling operation when outdoor temperatures are from 60°F to 32°F, consisting of a fan cycle switch and a crank case heater (*for 9/12K nominal circuits only*)
- **Hard start** shall be field installed
- **Copper-copper condenser coils** – for protection against galvanic corrosion (*consult factory for coating options*)